



# Seaboard Asphalt Products Company

## PRODUCT DATA

## ROOF AND FOUNDATION COATING

### LN-7 SEABOARD ROOF AND FOUNDATION COATING

#### PRODUCT DESCRIPTION:

Seaboard Roof and Foundation Coating meets ASTM-D-4479 Type I specifications and is 100% ASBESTOS-FREE. This material is an asphalt cutback fortified with fibres and additives.

#### BASIC USES:

Seaboard Roof and Foundation Coating is used as a cold applied system on commercial and private applications. This material is used as a protective coating for various roof types and a resaturant for old roofs. It is also used as a dampproofing and protective coating for concrete, masonry, and block walls as well as for metal tanks and concrete pipe.

#### LIMITATIONS:

DO NOT HEAT container.

#### APPLICATION:

Seaboard Roof and Foundation Coating must be applied to a dry surface free of foreign matter. This material can be applied with a roof brush, squeegee, or heavy duty commercial spray equipment and must be stirred before use. The coverage will vary per gallon on concrete or metal from 80-100 square feet to brick and mortar from 50-75 square feet to gravel or flat roofs from 25-50 square feet.

#### STORAGE:

Seaboard Roof and Foundation Coating can be used year round and the only protection would be from weathering on the container.

#### COMPOSITION:

Asphalt	CAS 8052-42-4
Mineral Spirits	CAS 64741-41-9
Fibre	CAS 65996-61-4
	CAS 9004-34-6
Amine Salt	CAS 30113-45-2
Clay	CAS 8031-18-3

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.

